

SPECIFICATIONS & FEATURES eMat Pro 100W/150W/200W

Overview

Bring an element of luxury to any tiled surface with the eMat Pro. This self-adhesive heating mat is specifically designed for fast and efficient installation directly onto concrete sub-based floors with minimal increase in floor height. The eMat Pro's twin conductor heating cable means there is no second tail to return to the thermostat, saving installation time and cost.

Specification

| Cable thickness | 3.5mm |
|---------------------------|---|
| Output | 100W/m ² 150W/m ² 200W/m ² |
| Operating Voltage | 230/240V |
| Cold tail connection lead | 4m flat PVC, PVC 2 core with earth braid |
| Outer Sheath | PVDF |
| Insulation | FEP |
| Standards | Intertek S-Mark |

Features

| 🗹 Se | lf-adhe | sive me | sh | | |
|------------|-----------------------|--|---|-------------------------------|--|
| 🗹 Ult | tra thin | heating | ı cable | | |
| 🗹 Tw | in conc | ductor h | eating cab | le | |
| 🗹 Su | itable f | or most | floor surfa | ces | |
| 1 0 | 0% alur | minium | earth shea | ith | |
| | | | | | <u> </u> |
| | | | | | (elements |
| | | | | ts | () <i>(</i>) |
| | | | | Ş | |
| | | | | Q | |
| | | (Here) | | E | |
| | Ø | | | U | 500 |
| AHIDAT | | | | | |
| | | | | | Hat Pro |
| | | | | | eMat Pro The thin self-adhesive heating mat |
| | | | | | www.elementsunderfloorheating.ca.uk |
| | | | | | and the second s |
| | ☑ Ult ☑ Tw ☑ Su | ✓ Ultra thin ✓ Twin conc ✓ Suitable feed | ✓ Ultra thin heating ✓ Twin conductor h ✓ Suitable for most | Suitable for most floor surfa | · · · · · · · · · · · · · · · · · · · |

Edison House Edison Close Ransomes Europark Ipswich, Suffolk IP3 9GU

Stitched

Tel: 01473 276677

(F

Self Adhesive

Backing

Fax: 01473 276678 Email: info@elementsunderfloorheating.co.uk Web: www.elementsunderfloorheating.co.uk



eGUARD

Intertek